



Delo® Protection for Construction Equipment

Hydraulic System

- Delo TorqForce™ SAE 10W (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce Syn SAE 5W-20
- Rando® HDZ



Bearings and Grease Points

- Delo Heavy Duty EP
- Delo Heavy Duty Moly 5% EP
- Delo Heavy Duty Synthetic Moly 5% EP

Transmissions

- Delo TorqForce SAE 30 (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo 400 SAE 10W (hydrostatic)



Engine Crankcase

- Delo 400 XSP SAE 5W-40
- Delo 400 XLE SAE 15W-40
- Delo 400 XLE SAE 10W-30
- Delo 400 SDE SAE 15W-40
- Delo 400 LE SAE 15W-40
- Delo 400 SD SAE 15W-30**



Coolant System

- Delo ELC Antifreeze/Coolant Premixed 50/50
- Delo XLC Antifreeze/Coolant Premixed 50/50

Differentials and Gear Drives

- Delo Syn-Gear XDM SAE 75W-90
- Delo Gear ESI SAE 80W-90
- Delo TorqForce SAE 50 (CAT TO-4)



Available as ISOCLEAN® Certified

**Severe duty applications typically have lower drain intervals relative to other duty cycles. See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in construction. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.



Delo®

Let's go further.™

A Chevron company product

©2017 Chevron U.S.A. Inc. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.

DLPTCNEQST_11-16